

KANMED^o WARMINGCABINET

ORDERING INFORMATION

Article / Ordering Numbers:	LARGE CABINET		SMALL CABINET		COMBINATION CABINET	TABLE TOP CABINET	
	Universal	Blanket Warming	Universal	Blanket Warming	Fluid and Blanket Warming	42°	60°
Cabinet with adjustable feet	GE-2350L	GE-2380L	GE-2350S	GE-2380S	GE-2350D	GE-2442	GE-2470
Shelf	GE-41500	-	GE-41500	-	GE-41500	-	-
Basket	GE-41600	-	GE-41600	-	GE-41600	-	-
Shelf Blanket Cabinet	-	GE-41580	-	GE-41580	GE-41580	-	-
Wheel Kit Large Cabinet	GE-41700	GE-41700	-	-	GE-41700	-	-
Wheel Kit Small Cabinet	-	-	GE-41900	GE-41900	-	-	-

ADDITIONAL INFORMATION

Outside measurements Height / Width / Depth	168 cm / 66 cm / 64 cm Height without wheels or feet		95 cm / 66 cm / 64 cm Height without wheels or feet		168 cm / 66 cm / 64 cm Height without wheels or feet	62cm / 51cm / 52cm
Inner volumes	≈415 litres	≈415 litres	≈190 litres	≈190 litres	≈160 + ≈160 litres	≈96 litres
Inside measurements Height / Width / Depth	140cm / 56cm / 53cm		65cm / 56cm / 53cm		≈59cm / 56cm / 53cm x 2	47cm / 43,5cm / 47cm
Height Feet / Height Wheels	Feet 13–18 cm. Wheels 16 cm. On the large Cabinets the front wheels extends 10 cm and add 2 x 13 cm to the total width.					Rubber feet
Voltages / Power max / Fuses	230 VAC ± 10% / ≈900W (1800W Combination Cabinet) / T6,3A / 10A 250V. 115 VAC 60Hz is also available. Please contact Kanmed.					230 VAC Grounded. Max power 400W.
Average power consumption	100–200 W	150–250 W	100–200 W	150–250 W	150–250 W	50 W
Possible number of baskets/shelves	10	5	5	2	4 in fluid compartment 2 in blanket compartment	1
Shelf Width/Dept/Height Weight (GE-41600)	52x50x2 cm 4 kg	49x53x1,2 cm 2,2 kg	52x50x2cm 4 kg	49x53x1,2 cm 2,2 kg	52x50x2 cm	-
Weight without shelves/baskets	≈130 kg	≈130 kg	≈100 kg	≈100 kg	≈140 kg	≈35 kg
Doors with magnetic handle	Doors can be hung left or right. Factory standard is left hung. Please specify when ordering. Right hung doors may add three weeks to delivery time.					Changeable Left/right
Max. load per shelf/basket	20 kg					10 kg
Warming Capacity	Warms 10 pieces Kanmed Gel Pads GE-455015 from 22°C – 40°C in less than 3 hours.					-
Temperature range	35°C – 50°C	35°C – 80°C	30°C – 50°C	30°C – 80°C	36°C – 50°C / 36°C – 80°C	35°C – 60°C
Accuracy	± 2°C	± 4°C	± 2°C	± 4°C	± 2°C / ± 4°C	± 2°C
Factory set maximum temperature	42°C	70°C	42°C	70°C	42°C / 70°C	42°C / 60°C

Other features /information: Made of high quality stainless steel. Polyurethane foam insulation for minimal heat leakage and optimal sound insulation. The door has double energy saving safety glass. Large and Small Universal Cabinets are equipped with rails for 10/5 shelves or baskets. Height between the shelves and baskets in the Universal Cabinet is ≈13 cm. In the Blanket Warming Cabinets the shelves can be moved up or down in steps of 13 cm.

Temperature regulation: Programmable electronic temperature regulator with display. Temperature can be blocked at a fixed value. A Capillary thermostat ensures independent over temperature prevention. A Bimetal thermostat is integrated in the heating element.

KANMED^o WARMINGCABINET

HIGH QUALITY WARMING CABINETS



Warming Cabinets that help to prevent perioperative hypothermia and increase patient comfort.



Warming Cabinets for patient comfort



Visit www.kanmed.se for more information and to find your local supplier for a trial.

KANMED^o

Kanmed AB

Gårdsfogdevägen 18B, SE-168 67 Bromma, Sweden
Telephone: +46 8 564 80 630. E-mail: info@kanmed.se
www.kanmed.se

EN/W/C/1905





KANMED^o WARMINGCABINET

Warming Cabinets that help to prevent perioperative hypothermia and to increase patient comfort.

The Kanmed Warming Cabinet is made in Sweden using stainless steel and high quality components. They are designed to withstand the hard use in a hospital environment.

A technician can easily change temperature limits, block temperatures, set high and low temp alarm limits, etc. to suit your requirements.

SPECIAL FEATURES

- Doors can be hung left or right
- Double insulating safety glass
- Low power consumption
- Very quiet
- Access to items is really easy
- Magnetic door handles
- Either height adjustable feet or lockable wheels
- Easy to clean
- 2 year warranty



” A warm blanket is an easy and safe method to increase patient comfort and reduce shivering before and after surgery ”

KANMED BLANKET WARMING CABINETS

Fast and economical warming of: Blankets, Towels, Sheets, etc.

The KANMED BLANKET WARMING CABINET is used in the pre operation and recovery area to warm blankets and other patient bedding material.

- A. Blanket Warming Cabinet Large art.no. GE-2380L (Max 4 shelves)
- B. Blanket Warming Cabinet Small art.no. GE-2380S (Max 2 shelves)

KANMED UNIVERSAL WARMING CABINETS

Intended for fast and economical warming of: Irrigation Fluids, Intravenous and Dialysis Fluids, Gel Pads, Gel positioning items, Instruments, etc.

The KANMED UNIVERSAL WARMING CABINET is designed to assist in the reduction of patient hypothermia and to increase the patient comfort. The Cabinets may be used everywhere in the hospital but they are mainly used in the operating theatre areas.

- C. Universal Warming Cabinet Small art.no. GE-2350S (Max 5 shelves or baskets)
- D. Universal Warming Cabinet Large art.no. GE-2350L (Max 10 shelves or baskets)



KANMED COMBINATION CABINET

A combination of a small Universal and a small Blanket Warming Cabinet.

The KANMED COMBINATION CABINET Max 4 shelves or baskets in the fluid compartment and 2 shelves in the blanket compartment.

- E. Combination Cabinet art. no. GE2350D



The Cabinet can be ordered with either height adjustable feet or lockable wheels.



KANMED TABLE TOP WARMING CABINET

Available in two versions:

For infusions, gels, etc. Pre-set to max 42°C
For blankets, towels, etc. Pre-set to max 60°C

KANMED TABLE TOP CABINET Features:

- High Quality
- Very low running and maintenance costs
- Long lifetime • Very well insulated
- Very low energy consumption
- Quiet • Easy to clean • Lockable door
- Includes one shelf

- F. Table Top Warming Cabinet 42° art.no. GE-2442
- Table Top Warming Cabinet 60° art.no. GE-2470